

JOINTER
SAFETY TEST

Date _____ Period _____ Name _____

Instructions: Select the best answer, then write that complete answer on the line shown.

1. Be careful that you do not run any material that might have _____
_____ in it over the jointer.
A. reverse grain C. long glue joints
B. open pitch pockets D. nails, screws, or loose knots
2. Always see that the jointer is set to the right depth of cut, about _____ inch, before you turn on the power.
A. 1/8 C. 3/16
B. 1/16 D. 1/32
3. In edge jointing a board, do not machine material that is less than _____ inch(es) square.
A. 1/2 C. 2
B. 1 D. 3/4
4. You must not use the jointer for face work which is less than _____ inch(es) thick.
A. 1/4 C. 1
B. 1/2 D. 2
5. You must not use the jointer for wood less than _____ inches long.
A. 6 C. 16
B. 12 D. 24
6. You must use _____ when jointing pieces less than 2 inches square.
A. finger pressure C. a metal tool
B. even pressure D. a push stick
7. You must always use a safety shoe or push block when jointing the _____ of a piece of material.
A. left edge C. face side
B. left side D. top side
8. Do not use the jointer for cuts deeper than _____ inch.
A. 1/32 C. 1/8
B. 1/16 D. 1/4
9. You should _____ change the adjustment of the rear or out feed table.
A. always C. sometimes
B. never D. accurately
10. Push stock over the jointer with a _____ motion (about 15 feet per minute).
A. very quick C. steady
B. slow D. both B and C
11. Stand _____ the jointer, not behind or in line with your material.
A. in the back, behind C. on the left, beside
B. near the front of D. at the rear of

12. Shift your hands so they never pass over the knife head _____.
- | | |
|--------------------------------|-----------------------------|
| A. at the beginning of the cut | C. at any time |
| B. on deep cuts | D. until the end of the cut |
13. When you cut _____ on the jointer, you must clamp a stop block to the fence or table to support the end of the board and prevent a kickback.
- | | |
|-----------|-----------|
| A. boards | C. edges |
| B. deeply | D. tapers |
14. Jointer should never be used for jointing _____.
- | | |
|---------------|-------------------|
| A. end grain | C. face surface |
| B. side grain | D. straight grain |
15. Any operation which requires a special set-up must be approved by the instructor _____ of the operation.
- | | |
|-----------------------|----------------------------------|
| A. after the start | C. during the process |
| B. prior to the start | D. at no time during the process |